

VANITY TOPS

- **Manufacturer**
Decra Ltd, 34 Forest Business Park, Argall Avenue, London E10 7FB
Tel: 020 8520 4371 Fax: 020 8521 0605 email: sales@decraltd.co.uk
- **Range**
Designer vanity tops, (type VPM/DMMR)
- **Tops**
18mm Moisture resistant medium density fibreboard
- **Facing**
Faced on one side with high-pressure laminate, balancing laminate on reverse.
Laminate to be from manufacturer's standard choice of 23 colours.
- **Edging**
Edging in high-pressure laminate to match facing laminate.
- **Dimensions**
For inset vanity basins: Front to back dimension to be 600mm o/a worktop. Post-formed apron (downstand) to be 200mm below surface of worktop, coved upstand to be 100mm above work surface.

For semi-recessed basins: Front to back dimension to be 300mm o/a worktop. Post-formed apron (downstand) to be 300mm below surface of worktop.
- **Options, at extra cost**
Support brackets
- **Underpanels**
19mm o/a Moisture-resistant melamine faced chipboard from manufacturer's standard choice of 23 colours.
- **Edging**
Edging to be 3mm thick PVC lipping, colour co-ordinated to facing
- **Method of fixing panels**
Lift-off secret-fixing clips to suit Decra system
- **Joint treatment**
Vertical joints to suit design module
- **Flash gaps**
High-pressure laminate strips
- **Other requirements**
PAR softwood framework by main contractor, to include 100mm high plywood skirting. Allow for extra bracing to support urinals, washbasins and cisterns.