

CUBICLE PARTITIONS / PANEL CUBICLES

- **Manufacturer**
Decra Ltd, 34 Forest Business Park, Argall Avenue, London E10 7FB
Tel: 020 8520 4371 Fax: 020 8521 0605 email: sales@decraplastics.co.uk

- **Reference**
Stratum V cubicles

- **Pilasters**
44 mm o/a thickness panels constructed from wood veneer on a moisture-resistant particleboard core. Vertical edges rebated hardwood; other edges square, lipped with veneer. A/C lacquer finish

- **Doors & overpanels**
44 mm o/a thickness panels constructed from wood veneer on a moisture-resistant particleboard core. A/C lacquer finish. Vertical edges in hardwood; closing stiles rebated; all other edges square.

Door & overpanel to be made as a set so that woodgrain runs through.

- **Partitions**
19 mm o/a thickness panels constructed from wood veneer on a moisture-resistant particleboard core. Exposed edges lipped to match.

- **Ironmongery/accessories**
100 mm stainless steel foot support, stainless steel rotary indicator bolt with external emergency release facility, pivot hinges with anti finger trap, door closing buffers.

- **Other requirements**
Overall cubicle height to be 2350 mm above finished floor level including 100mm floor clearance & 50 mm ceiling clearance. Actual door height to be 1960 mm above ffl.