

## CUBICLE PARTITIONS / PANEL CUBICLES

- **Manufacturer**  
Decra Ltd, 34 Forest Business Park, Argall Avenue, London E10 7FB  
Tel: 020 8520 4371 Fax: 020 8521 0605 email: [sales@decraplastics.co.uk](mailto:sales@decraplastics.co.uk)
- **Reference**  
Symetria 2350 cubicles
- **Pilasters**  
130 mm extruded aluminium section with flat front. Section to be powder-coated to a colour from manufacturer's standard range
- **Headrail**  
Slim extruded aluminium section with rounded front. Section to be powder-coated to a colour from manufacturer's standard range
- **Panels & doors**  
13mm o/a thickness compact laminate from manufacturer's standard choice of 23 colours.
- **Edging**  
Black, self edged & machined to a crescent.
- **Overpanel**  
Sand-blast effect acrylic panel
- **Ironmongery/accessories**  
Foot support; indicator bolt with external emergency release facility; door-closing buffers; pivot hinges with anti-finger trap feature; metal security screw fittings. All metalwork to be stainless steel (hinges to be stainless steel effect). Aluminium wall channels to be powder-coated or satin anodised.
- **Other requirements**  
Overall cubicle height to be 2350 mm above finished floor level with 20mm floor clearance. Actual door height to be 1940 mm (1960 mm above FFL)
- **Options (may involve extra cost)**  
Full height doors  
Doors with matching overpanel instead of acrylic overpanel  
Foot support & floor clearance at 100mm or 150mm