

## VANITY TOPS

- **Manufacturer**  
Decra Ltd, 34 Forest Business Park, South Access Road, London E17 8BA  
Tel: 020 8520 4371 Fax: 020 8521 0605
- **Range**  
Director vanity tops (type VPM/DL)  
To be compatible with the Director cubicle system
- **Tops**  
18mm Moisture resistant medium density fibreboard
- **Facing**  
Faced on one side with high-pressure laminate, balancing laminate on reverse.  
Laminate to be from manufacturers standard choice of 23 colours.
- **Edging**  
Edging in high-pressure laminate to match facing laminate
- **Dimensions**  
For inset vanity basins: Front to back dimension to be 600mm o/a worktop. Post-formed apron (downstand) to be 200mm below surface of worktop, coved upstand to be 100mm above work surface.  
  
For semi-recessed basins: Front to back dimension to be 300mm o/a worktop. Post-formed apron (downstand) to be 300mm below surface of worktop.
- **Options at extra cost**  
Support brackets
- **Underpanels**  
17mm o/a Moisture-resistant chipboard
- **Facing**  
Faced with high-pressure laminate from manufacturer's standard choice of 23 colours.  
Counterbalance laminate to reverse.
- **Edging**  
Edging to be high-pressure laminate to match facing.
- **Method of fixing panels**  
Lift-off secret-fixing clips to suit Decra system
- **Joint treatment**  
Vertical joints to suit design module.
- **Flash gaps**  
High pressure laminate strips
- **Other requirements**  
PAR softwood framework by main contractor, to include 100mm high plywood skirting